

(19) World Intellectual Property
Organization
International Bureau



25 FEB 2005

(43) International Publication Date
11 March 2004 (11.03.2004)

PCT

(10) International Publication Number
WO 2004/020781 A1

(51) International Patent Classification⁷: E21B 33/038

(21) International Application Number:
PCT/EP2003/009699

(22) International Filing Date:
1 September 2003 (01.09.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
202 13 388.5 30 August 2002 (30.08.2002) DE

(71) Applicant (for all designated States except US): COOPER
CAMERON CORPORATION [US/US]; 1333 West
Loop South, Suite 1700, Houston, TX 77027-9109 (US).

(72) Inventor; and

(75) Inventor/Applicant (for US only): BIESTER, Klaus
[DE/DE]; Am Maschsee 2, 29342 Wienhausen (DE).


(74) Agent: HILGERS, Hans; Grünecker, Kinkeldey, Stock-
mair & Schwanhäusser, Maximilianstrasse 58, 80538
München (DE).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC,
SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,
UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: CONNECTING MECHANISM



(57) **Abstract:** A connecting mechanism (1) for two parts (2, 3), which are at least partially insertable into one another, presents a cam-operated component (6), which runs on bearings and which is adjustable between a passive and an active position (4, 5), on the one part (2), for shifting a number of contact elements (7, 8, 9) between a withdrawal and a contact position (10, 11), whereby the contact elements (7, 8, 9), when in the contact position (11), mesh in a retaining indentation (12) on the other part (3), and a driving device (13) for the adjustment of the cam-operated component (6) between the active and passive positions (4, 5). In order to ensure a secure and stable connection of these parts, using simple design means without additional pre-stressing or restraining devices, even when the parts are only partially inserted into one another, the contact elements (7, 8, 9) are arranged in two or more levels (14, 15, 16) essentially parallel to the insertion direction (17) of the two parts (2, 3) and the cam-operated component (6) for shifting the contact elements (7, 8, 9) between the withdrawal and contact positions (10, 11) is allocated to each level (14, 15, 16).

WO 2004/020781 A1